

MOTOTECH SS 10W-30



PRODUCT DESCRIPTION

A semi-synthetic, fuel-efficient engine oil crafted from premium base stocks and advanced additives. It delivers excellent flow and high lubricity to reduce friction and engine wear.

Optimised for cold-start protection and reliable hydraulic tappet performance, it ensures smooth operation during idling and stop-start driving, extending engine life and supporting fuel economy.

BENEFITS

- Enhances fuel efficiency.
- Excellent oxidation protection.
- High shear stability ensures stay-in-grade performance.
- Minimises corrosion, varnish, and sludge formation.
- Outperforms conventional mineral oils.
- Semi-synthetic formulation.

APPLICATIONS

Suitable for petrol and diesel vehicles including engines with fuel injection systems or turbochargers. Recommended for vehicles with or without exhaust emission aftertreatment devices.

TYPICAL TEST DATA

Appearance	-	Clear&bright,undyed
Density @ 15°C	-	0.86
Flash Point (°C)	-	200
Kinematic Viscosity @ 40°C (mm²/s)	-	68
Kinematic Viscosity @ 100°C (mm²/s)	-	11.5
Pour Point (°C)	-	-30
Total Base Number (mg KOH/g)	-	7
Viscosity Index	-	140

RECOMMENDED BY MOTOSHIELD OILS AS SUITABLE FOR THE FOLLOWING APPLICATIONS

API	SN/CF
ILSAC	GF-5