

MOTOTECH SS 10W-40



PRODUCT DESCRIPTION

A high-quality multigrade engine oil formulated from a balanced blend of premium mineral and synthetic base stocks and advanced additive technology. It provides excellent lubricity to help reduce internal friction and engine wear, while enhanced low-temperature fluidity promotes rapid oil circulation and improved hydraulic tappet response during cold starts, supporting smooth operation and reliable protection across a wide range of operating conditions.

BENEFITS

- Advanced anti-wear technology helps protect engine components.
- Excellent protection against oxidation.
- High shear stability supports stay-in-grade performance.
- Reduces corrosion, varnish and sludge formation.
- Superb thermal stability at high operating temperatures.

APPLICATIONS

Suitable for petrol and diesel vehicles including engines with fuel injection systems or turbochargers. Recommended for vehicles without exhaust emission aftertreatment devices.

TYPICAL TEST DATA

Appearance	-	Clear&bright,undyed
Density @ 15°C	-	0.87
Flash Point (°C)	-	220
Kinematic Viscosity @ 40°C (mm²/s)	-	95
Kinematic Viscosity @ 100°C (mm²/s)	-	13.8
Pour Point (°C)	-	-20
Total Base Number (mg KOH/g)	-	10
Viscosity Index	-	147

RECOMMENDED BY MOTOSHIELD OILS AS SUITABLE FOR THE FOLLOWING APPLICATIONS

ACEA	A3/B3, A3/B4
API	SN/CF
Mercedes-Benz	229.1/229.3
Renault	RN0700/RN0710
VW	502.00/505.00